













- Corrosion resistant zinc finish
- · Hardened double ball raceways
- Operating temperature rating -45°F to 180°F
- Ultra-tough, thermoplastic wheel resists hard impacts and supports high dynamic load



Typical Applications


 Vending machines, computer racks, server cabinets or anywhere overall load height is restricted

Performance Options

• Consult factory for rigid, brake and additional finish options


Business Machine Casters • 500 lb Top Plate

Whe Dia	el Tread . Width	Capacity Each (Pounds)	Wheel Descriptions	Wheel Bearing	Swivel Top Plate Caster Models	Load Height	Swivel Radius	Weight lbs
3"	1 ¹³ / ₁₆ '	500	Glass Filled Nylon	Roller	S4.3305.351	41/8"	2 ³ /4"	21/4



Business Machine Casters • 700 lb Top Plate

Wheel Dia.	Tread Width	Capacity Each (Pounds)	Wheel Descriptions	Wheel Bearing	Swivel Top Plate Caster Models	Load Height	Swivel Radius	Weight lbs
3"	1 ¹³ /16"	700	Glass Filled Nylon	Roller	S4.3307.351	3 31/32"	2 3/4"	2 ¹ /2



Business Machine Casters • 1200 lb Top Plate

Wheel Dia.	Tread Width	Capacity Each (Pounds)	Wheel Descriptions	Wheel Bearing	Swivel Top Plate Caster Models	Load Height	Swivel Radius	Weight Ibs
3"	1 ¹³ / ₁₆ "	1200	Glass Filled Nylon	Roller	S4.3312.351	4 1/8	2 1/2	3

