

# RETORT WHEELS

**MADE** in the USA and more cost-competitive than ever

**DESIGNED** to withstand higher temperatures-up to 290 degrees continuous

**MANUFACTURED** with a heat-stabilized, impact modified, glass-filled polypropylene for lasting durability

**WHITE** color for simple visual confirmation of cleanliness



HEAT RESISTANT



## GLASS-FILLED POLYPROPYLENE – Up to 900-lb. Load Capacity

Designed to withstand the rigors of high temperatures, Retort wheels are perfect for cooker racks and retort carts. Also ideal for use in food processing and medical applications where high-heat cleaning or sanitation is required.

### GLASS-FILLED POLYPROPYLENE TREAD

**Wheel Face:** Moderate crown  
**Finish:** White

**Temperature Range:** -20°F degrees up to 290°F continuous  
**Hardness:** 75 Shore D

Wheel Diameter (Inches)	Tread Width* (Inches)	Load Capacity (Pounds)	Hub Length (Inches)	Bore ID (Inches)	Bearing ID (Inches)	Wheel Number Roller Bearing	Wheel Number Plain Bore
4	2	500	2-3/16	3/4			5.00004.832RW
		500	2-3/16	1-3/16	3/4	5.00004.839RW	5.00004.836RW
5	2	650	2-3/16	3/4			5.00005.832RW
		650	2-3/16	1-3/16	3/4	5.00005.839RW	5.00005.836RW
6	2	700	2-3/16	3/4			5.00006.832RW
		700	2-3/16	1-3/16	3/4	5.00006.839RW	5.00006.836RW
8	2	900	2-3/16	3/4			5.00008.832RW
		900	2-3/16	1-3/16	3/4	5.00008.839RW	5.00008.836RW

\*Also available in 1-1/4" and 1-1/2" tread width.



DOWNLOAD  
**3D CAD MODELS**  
 & DATASHEETS

ONLINE  
[www.ColsonCaster.com](http://www.ColsonCaster.com)  
 (800-643-5515)

APP STORE  
 Search: "Caster CAD 3D"

